



CONSTRUCTION

- 1- Conductor:** Compact class B stranded soft annealed bare copper as per ASTM B-496.
- 2- Conductor shield:** Extruded thermoset semi-conducting stress control layer.
- 3- Insulation:** Ethylene propylene rubber (EPR).
- 4- Insulation shield:** Extruded thermoset strippable semi-conducting insulation shield.
- 5- Copper wires shield:** One-third neutral concentric round annealed bare copper wires helically applied over the insulation shield.
- 6- Jacket:** black flame retardant, sunlight and oil resistant I polyvinyl chloride (PVC)

FEATURES AND APPLICATIONS

- EPRONAX type MV-90 is suitable for use in wet or dry locations, in open air (exposed to sunlight), raceways, troughs, ducts and direct burial.
- Typical installations include feeder or branch circuits in generating stations, industrial and commercial installations.
- Rated at maximum operating temperature of 90 °C for normal operation, 130 °C for emergency overload and 250 °C for short-circuit conditions.
- True triple and dry curing extrusion system.
- Excellent flexibility.
- Excellent corona and moisture resistance.
- Cold bend tested at -35 °C.
- NEC guidelines must be followed for proper application.
- FT4 (70,000 BTU/hr) Flame test and CT use (1/0 AWG and larger).
- UL listed as MV-90 under file E-500191.

STANDARDS

ASTM B-3 - Standard Specification for Soft or Annealed Copper Wire

ASTM B-496 - Standard Specification for Compact Round Concentric-Lay-Stranded Copper Conductors.

UL 1072 - Medium-Voltage Power Cables.

ICEA S-93-639 - 5-46 kV Shielded Power Cable for use in the Transmission and Distribution of Electric Energy

UL 1685 - Safety Vertical-Tray Fire-Propagation and Smoke-Release Test for Electrical and Optical-Fiber Cables

IEEE 1202 – Flame-propagation testing of wire and cable.

COPPER CONDUCTOR, 8 kV 100 % INSULATION LEVEL, 115 MILS

PRODUCT CODE	COND. SIZE (AWG or kcmil)	NOMINAL CONDUCTOR DIAMETER (inches)	NOMINAL INSULATION DIAM. (inches)	NOMINAL INSULATION SHIELD DIAM. (inches)	NOMINAL DIAMETER OVER JACKET (inches)	APPROX. WEIGHT (lb/kft)		AMPACITY (A)			CONDUIT SIZE (inches)
						COPPER	TOTAL	CONDUIT IN AIR (1)	UNDERGROUND DUCT (2)	TRAY (3)	
836601045	4	0.21	0.518	0.581	0.873	488	1103	110	115	---	3
836601047	2	0.27	0.572	0.635	0.927	662	1341	150	155	---	3
836601048	1	0.30	0.604	0.667	0.959	815	1527	170	175	---	3
836601049	1/0	0.33	0.641	0.704	0.996	1032	1781	195	200	195	3
836601050	2/0	0.37	0.680	0.743	1.035	1291	2078	225	230	225	3
836601051	3/0	0.42	0.727	0.790	1.082	1630	2461	260	260	260	3
836601052	4/0	0.47	0.781	0.844	1.136	2066	2945	295	295	300	3 ½
836601053	250	0.52	0.824	0.887	1.179	2433	3352	330	325	335	3 ½
836601054	350	0.61	0.919	0.981	1.274	3390	4390	395	390	415	4
836601057	500	0.73	1.041	1.104	1.496	4868	6158	480	465	515	5
836601060	750	0.90	1.206	1.269	1.722	7359	8978	585	565	665	5
836601062	1000	1.06	1.361	1.424	1.877	9752	11523	675	640	795	6

COPPER CONDUCTOR, 8 kV 133 % INSULATION LEVEL, 140 MILS

PRODUCT CODE	COND. SIZE (AWG or kcmil)	NOMINAL CONDUCTOR DIAMETER (inches)	NOMINAL INSULATION DIAM. (inches)	NOMINAL INSULATION SHIELD DIAM. (inches)	NOMINAL DIAMETER OVER JACKET (inches)	APPROX. WEIGHT (lb/kft)		AMPACITY (A)			CONDUIT SIZE (inches)
						COPPER	TOTAL	CONDUIT IN AIR (1)	UNDERGROUND DUCT (2)	TRAY (3)	
838501045	4	0.21	0.569	0.631	0.924	488	1183	110	115	---	3
838501047	2	0.27	0.622	0.685	0.978	662	1426	150	155	---	3
838501048	1	0.30	0.654	0.717	1.009	815	1615	170	175	---	3
838501049	1/0	0.33	0.691	0.754	1.046	1032	1872	195	200	195	3
838501050	2/0	0.37	0.731	0.794	1.086	1291	2173	225	230	225	3
838501051	3/0	0.42	0.777	0.840	1.132	1630	2560	260	260	260	3 ½
838501052	4/0	0.47	0.831	0.894	1.186	2066	3049	295	295	300	3 ½
838501053	250	0.52	0.874	0.937	1.230	2433	3460	330	325	335	3 ½
838501054	350	0.61	0.969	1.032	1.324	3390	4507	395	390	415	4
838501057	500	0.73	1.091	1.154	1.547	4868	6293	480	465	515	5
838501060	750	0.90	1.256	1.319	1.772	7359	9134	585	565	665	5
838501062	1000	1.06	1.412	1.475	1.928	9752	11692	675	640	795	6

(1) Ampacities are in accordance with table 310.60(C)(74) of the NEC for insulated triplexed or three single-conductor aluminum cables in isolated conduit in air based on conductor temperatures of 90°C (194°F) and ambient air temperature of 40°C (104°F).

(2) Ampacities are in accordance with table 310.60(C)(78) of the NEC for three single-insulated aluminum conductors in underground electrical ducts (three conductors per electrical duct) based on ambient earth temperature of 20°C (68°F) electrical duct arrangement in accordance with figure 31060 detail 1 100 percent load factor thermal resistance (rho) of 90 conductor temperatures of 90°C (194°F).

(3) Ampacities are in accordance with Section 392.80(B)(2) of the NEC for single Type MV-90 conductor cables or single conductors cabled together (triplexed, quadruplexed, etc) installed in uncovered cable tray at ambient temperature of 40°C (104°F) and conductor temperatures of 90°C (194°F). The ampacities shall not exceed 75 percent of the allowable ampacities in Table 310.60(C) (70). Where the cable trays are covered for more than 18 m (6 ft) with solid unventilated covers the ampacities for 1/0 AWG and larger single conductor cables shall not exceed 93 percent of the values shown above. Jam ratio has not been considered and should be checked to avoid possible jamming.

Values are nominal and subject to manufacturing tolerances.