



CONSTRUCTION

- 1- Conductor:** Compact class B stranded soft annealed bare copper as per ASTM B-496.
- 2- Conductor shield:** Extruded thermoset semi-conducting stress control layer.
- 3- Insulation:** Tree-retardant cross-linked polyethylene (TR-XLPE).
- 4- Insulation shield:** Extruded thermoset strippable semi-conducting insulation shield.
- 5- Copper wires shield:** one-third neutral concentric round annealed bare copper wires helically applied over the insulation shield.
- 6- Jacket:** black flame retardant, sunlight and oil resistant I polyvinyl chloride (PVC).

FEATURES AND APPLICATIONS

- INDULINK type MV-90 is suitable for use in wet or dry locations, in open air (exposed to sunlight), raceways, troughs, ducts and direct burial.
- Typical installations include feeder or branch circuits in generating stations, industrial and commercial installations.
- Rated at maximum operating temperature of 90 °C for normal operation, 130 °C for emergency overload and 250 °C for short-circuit conditions.
- Superior current carrying capacity.
- True triple and dry curing extrusion system.
- Excellent flexibility.
- Excellent corona and moisture resistance.
- Cold bend tested at -35 °C.
- NEC guidelines must be followed for proper application.
- UL listed as MV-90 under file E-500191.

STANDARDS

ASTM B-3 - Standard Specification for Soft or Annealed Copper Wire.

ASTM B-496 - Standard Specification for Compact Round Concentric-Lay-Stranded Copper Conductors.

UL 1072 - Medium-Voltage Power Cables.

ICEA S-93-639 - 5-46 kV Shielded Power Cable for use in the Transmission and Distribution of Electric Energy.

COPPER CONDUCTOR, 35 kV 100 % INSULATION LEVEL, 345 MILS

PRODUCT CODE	COND. SIZE (AWG or kcmil)	NOMINAL CONDUCTOR DIAMETER (inches)	NOMINAL INSULATION DIAM. (inches)	NOMINAL INSULATION SHIELD DIAM. (inches)	NOMINAL DIAMETER OVER JACKET (inches)	APPROX. WEIGHT (lb/kft)		AMPACITY (A)		CONDUIT SIZE (inches)
						COPPER	TOTAL	CONDUIT IN AIR (1)	UNDERGROUND DUCT (2)	
821901049	1/0	0.33	1.081	1.144	1.436	1032	1081	195	200	4
821901050	2/0	0.37	1.120	1.183	1.476	1291	1223	225	230	5
821901051	3/0	0.42	1.167	1.230	1.522	1630	1406	260	260	5
821901052	4/0	0.47	1.221	1.284	1.576	2066	1636	295	295	5
821901053	250	0.52	1.264	1.327	1.619	2433	1829	330	325	5
821901054	350	0.61	1.359	1.422	1.774	3390	2386	395	390	5
821901057	500	0.73	1.481	1.544	1.996	4868	3220	480	465	6
821901060	750	0.90	1.646	1.709	2.162	7359	4449	585	565	6
821901062	1000	1.06	1.802	1.865	2.317	9752	5631	675	640	7

(1) Ampacities are in accordance with table 310.60(C)(73) of the NEC for insulated triplexed or three single-conductor copper cables in isolated conduit in air based on conductor temperatures of 90°C (194°F) and ambient air temperature of 40°C (104°F).

(2) Ampacities are in accordance with table 310.60(C)(77) of the NEC for three single-insulated copper conductors in underground electrical ducts (three conductors per electrical duct) based on ambient earth temperature of 20°C (68°F) electrical duct arrangement in accordance with figure 31060 detail 1 100 percent load factor thermal resistance (rho) of 90 conductor temperatures of 90°C (194°F).

Jam ratio has not been considered and should be checked to avoid possible jamming.

Values are nominal and subject to manufacturing tolerances.